



## High Performance Pothole Repair

Colquick is a ready-to-use cold mix that hardens, with the addition of water, to quickly attain the performance of hot mix.

- Developed for spot repairs and small maintenance jobs
- Ideal for situations where a quick repair and re-opening to traffic is important
- Perfect for filling potholes, localized re-profiling, trench repairs, sidewalk and bike trail maintenance
- Repairs are long-lasting, even under heavy traffic conditions, without rutting or punching out
- Sets up in 30 minutes and attains the performance of hot mix asphalt in 24 hours

# Colquick is ready to use right out of the pail!

The repair is simple, easy and long-lasting when using the following procedure.

- 1** Sweep to remove free-standing water and loose material.
- 2** Pour Colquick in the pothole or on the area to be repaired.
- 3** Water the surface of the mix moderately and evenly.
  - Two cups of water activates a 22.7 kg pail. This is about 2% of the weight of the Colquick.
  - The water activates the material to initiate set-up.
  - Excess water delays the setting of Colquick.
- 4** Spread with a rake or shovel and compact.
  - Compaction can be done with a hand-held tamper.
  - For repairing larger areas, one can use a vibrating plate packer.
  - For small repaired surfaces, and depending on the ambient weather conditions, traffic can be resumed 15 to 45 minutes after compaction.
  - Cold temperatures increase the time it takes to set-up.

Partial buckets will last longer in dry environments when sealed and stored properly.

## Colquick is easy, convenient patching material

- Applicable for all asphalt wearing courses in all types of traffic conditions (even heavy tractor/trailer units).
- Currently available in an easy to use 22.7 kg (50 lb) pail.



Emits no VOCs as it contains no diluents or volatile compounds



# colquick

